

軸流ファン Axial Fan

40×40×20mm SERIES



- * Material Impeller & Frame : Plastic (UL 94V-0)
- * Lead Wires : UL 1007AWG # 26 or Equivalent
Red Wire Positive (+)
Black Wire Negative (-)
- * Impeller : 9 Blades
- * Rotational direction CCW view from inlet face
- * Weight : 30g (1.06oz)

SPECIFICATION : B : 2 Ball Bearings S : Sleeve
N : Nanometer Bearing
Frame Type : P : Flange Type (8 holes)
T : Rib Type (4holes)
Other Specially Design Type

型号	轴承	输入电压	电压范围	电流	功率	转速	风量	风压	噪音		
PART NO.	B. S. N	VDC	VDC	Amp	Watt	R. P. M	m ³ /min	CFM	mm Aq	INAq	dB-A
DG1204L	S	12	5~13.8	0.04	0.48	3000	0.11	3.87	1.64	0.065	18.2
DG1204M	S	12	5~13.8	0.05	0.60	4000	0.13	4.68	2.24	0.089	20.5
DG1204H	S	12	5~13.8	0.07	0.84	5000	0.16	5.60	3.34	0.131	24.0
DG1204G	S	12	5~13.8	0.09	1.08	6000	0.19	6.68	5.01	0.197	28.5
DG1204U	S	12	5~13.8	0.12	1.44	7000	0.22	7.64	6.16	0.243	32.5

- * Function type is optional
- * The max. air flow and the speed are measured in free air;
max Air pressure is measured at zero air flow.
- * Noise is measured in semi anechoic chamber in free air,
one meter from intake side.
- * All readings are typical values at rated voltage.
- * Specifications are subject to change without notice.

